

Product Specifications

ISA-bus to 3.5" 2 PCMCIA PC cards Card-Drive

R323CS00653GBH03R



Features :

- ❖ Internal ISA-bus interface card
- ❖ Standard 3.5" drive form-factor
- ❖ 2 front slots in PCMCIA type III
- ❖ Comply with PCMCIA V2.1/JEDIA 4.2
- ❖ Support read/write MS-FFS II/True FFS
- ❖ LED indicator
- ❖ RoHS compliant

Specifications :

❖ Host interface	Internal ISA-bus card
	Dimension 170.0 (L) * 99.2 (W) * 18.5 (H) mm
	Weight G. W.: 350g
❖ Card drive form-factor	Standard 3.5" drive mounted in the front of PC casing
	Dimension 150.6 (L) * 101.8 (W) * 25.3 (H) mm
	Weight G. W.: 150g
❖ Controller	VG469LF PCMCIA controller chip
❖ Standard	PCMCIA socket and card service drivers are fully compatible with PCMCIA v2.1
❖ Slot capabilities	2 front slots in PCMCIA type III
❖ Supported card type	16-bit PC card; PCMCIA SRAM card, PCMCIA linear flash card, ATA HDD, ATA flash card and most PCMCIA I/O card
❖ Power voltage	3.3V/5V
❖ Environmental specification	Operating Temperature 0°C ~ 70°C
	Non-operating Temperature -20°C ~ 80°C
	Relative Humidity Max 90%
❖ Booting function	Yes but need booting ROM
❖ Hot swap function	Yes and no software/drivers needed
❖ Driver	DOS driver needed, but Windows auto detected
❖ Supported OS	DOS, Windows 98/ME/NT/2000/XP & Lunix
❖ Warranty	1 year

Part Number List :

R323CS00653GBH03R	ISA-bus 3.5" standard PCMCIA card drive with 2front PCMCIA type III