

PHANES-K Series

aSLC SATA III CFast™ card



Product Feature

- aSLC - NAND type flash technology
- Optional rugged metal frame
- S.M.A.R.T. supported
- RoHS & REACH compliant
- Capacity from 16GB up to 64GB

Product Specification

Compatibility

- SATA Revision 3.2
- CFast™ Specification v2.0
- Compliant with ATA/ATAPI-8 ACS2

Flash technology

- aSLC-NAND type flash memory

Form-factor

- CFast™ Type I

Host Interface

- 7 pins (data) + 17 pins (power)
CFast™ connector

Performance

- Data transfer rate ■ SATA 1.5Gbps/3.0Gbps/6.0Gbps data transfer rate
- Sequential read ■ 555 MB/sec (Max.)
- Sequential write ■ 465 MB/sec (Max.)

Environmental specification

- Operating temp. ■ STD. 0°C~70°C/W.T. -40°C~+85°C
- Non-operating temp. ■ STD. -20°C~+80°C/W.T. -50°C~+95°C

Conformal coating

- Humidity ■ 10% ~ 95% non-condensing
- Vibration ■ 80 Hz to 2K Hz, 20G, 3 axes
- Shock ■ 0.5ms, 1500 G, 3 axes
- Altitude ■ 70,000 feet

Power consumption

- Power requirement ■ +3.3V±5%
- Reading mode ■ 1090 mW (Max.)
- Writing mode ■ 1475 mW (Max.)
- Idle mode ■ 260 mW (Max.)

Reliability

- Wear-leveling ■ Static and Dynamic wear-leveling algorithms
- Erase counts ■ Up to 20,000 times
- ECC ■ Designed with hardware LDPC ECC engine with hard-decision and soft-decision decoding.

Physical specification

- Weight ■ Plastic frame CFA : 10.0 ± 1 g / 0.40 oz.
- Rugged metal frame CFA : 13.0 ± 1 g / 0.46 oz.
- Dimension(W x L x H) ■ 42.8 x 36.4 x 3.5 (mm)

Warranty

- aSLC(standard/wide temp.) ■ 2 years or within 20K Erasing counts

Part Number List

Standard plastic frame CFA ▶

Product Picture	Capacity	0°C ~ 70°C	- 40°C ~ + 85°C
	16GB	SPCFA016G-PKCTMAS-(T)	WPCFA016G-PKCTMAS-(T)C
	32GB	SPCFA032G-PKCTMAS-(T)	WPCFA032G-PKCTMAS-(T)C
	64GB	SPCFA064G-PKCTMAS-(T)	WPCFA064G-PKCTMAS-(T)C

Optional rugged metal frame CFA ▶

Product Picture	Capacity	0°C ~ 70°C	- 40°C ~ + 85°C
	16GB	SRCFA016G-PKCTMAS-(T)	WRCFA016G-PKCTMAS-(T)C
	32GB	SRCFA032G-PKCTMAS-(T)	WRCFA032G-PKCTMAS-(T)C
	64GB	SRCFA064G-PKCTMAS-(T)	WRCFA064G-PKCTMAS-(T)C

Part Number Decoder

X1 X2 X3 X4 X5 X6 X7 X8 X9 — X11 X12 X13 X14 X15 X16 X17 — X19 X20

Example ▶

W R C F A 0 6 4 G — P K C T M A S — C

X1 Grade

S : Standard grade operating temp. 0° C~70 ° C

W : Wide temp. grade operating temp. -40° C~+85 ° C

X2 The material of casing

P : Plastic frame

R : Rugged metal frame

X3 X4 X5 Product category

CFA : CFast™ card

X6 X7 X8 X9 Capacity

016G : 16GB

032G : 32GB

064G : 64GB

X11 Controller

P : PHANES Series

X12 Controller version

A, B, C, D,

X13 Controller grade

C : Commercial grade

X14 Flash IC brand

T : Toshiba NAND flash IC

X15 Flash IC type

M : MLC-NAND flash IC

X16 X17 aSLC Technology

AS : aSLC Technology extends MLC product's lifespan

X19 X20 Reserved for specific requirement

Blank : Standard product w/o thermal sensor and conformal-coating

T : Thermal Sensor.

C : Conformal coating for wide temp. grade