

❖ Features



- 2.5" adapter without casing
- Dual CF type II sockets to 40-pin and 44-pin IDE
- Master/Slave selectable
- With a 4-pin power connector
- Bootable

❖ Specification

<ul style="list-style-type: none"> ■ Form-factor 2.5" form-factor with 4 standard 2.5" HDD Fixed holes ■ Declaration RoHS & REACH compliant ■ Host interface 40-pin (2.54mm pitch) male IDE connector *1 44-pin (2.00mm pitch) male IDE connector *1 ■ CF Socket CompactFlash® type II socket with ejector ■ Support CF Card type CompactFlash® card type I/II and MicroDrive ■ Power Connector 40-pin IDE adapter equipped with a 4-pin floppy power connector ■ Master/Slave Setting By jumper ■ Data Transfer Mode Support PIO-4 mode, MWDMA-2 mode and up to UDMA-6 mode ■ LED Indicator Optional for special request 	<ul style="list-style-type: none"> ■ Bootable Yes ■ Hot Swappable No ■ Operation Voltage +5V ■ Environmental <ul style="list-style-type: none"> ➢ Operating Temperature 0°C~+70°C ➢ Non-operating Temperature -20°C~+80°C ➢ Relative Humidity Max 90% ■ Supported O.S. DOS, Windows / Linux and O.S. ■ Dimension 70.1 mm x 78.1 mm ■ Weight (Max.) 55g ■ Warranty 1 year
---	---

❖ Part Number List

- **AD-CF24HIDE04003R** Host side horizontal type 44-pin IDE male connector to CF type II socket * 2

❖ Part Number Decoder

X1	X2	—	X4	X5	X6	X7	X8	X9	X10	X11	X12	X13	X14	X15	X16	X17	X18	X19	X20
----	----	---	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Example

A	D	—	C	F	2	4	H	I	D	E	0	4	0	0	3	R			
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--	--	--

X1 X2 Adapter

AD : Adapter series

X4 X5 Slot for card type

CF : CompactFlash® card
CA : CFast™ card

X6 X7 Slot number and type

11 : 1 slot of CompactFlash® type I
12 : 1 slot of CompactFlash® type II
24 : 2 slots of CompactFlash® type II

X8 Adapter form-factor

8 : 1.8 form-factor
5 : 2.5 form-factor
3 : 2.5 form-factor w/ standard 3.5" drive bay
R : 2.5 form-factor w/metal rear bracket
V : Vertical type
H : Horizontal type

X9 X10 X11 X12 X13 Host interface

IDE04 : 40-pin IDE connector + 44-pin IDE connector
SATA 1 : SATA I 1.0a
SATA 2 : SATA I 1.0a and SATA II 2.0
SATA 3 : SATA I 1.0a & SATA II 2.0 & SATA III 3.0

X14 X15 X16 APRO Internal code

X17 RoHS compliant

R : RoHS compliant

SLC
aSLC
MLC
3D-NAND
DRAM Module
Adapter
Card-drive