



❖ Features

- SLC-NAND flash technology
- Optional rugged metal frame
- Support Trim command set
- Support Native Command Queuing (NCQ)
- Support S.M.A.R.T. command set and utility
- Capacities from 1GB up to 2GB

❖ Specification

- **Compatibility**
 - SATA Revision 3.0
 - CFast™ Specification v2.0
 - ATA-8 command set
- **Declarations**
 - RoHS & REACH compliant
- **Flash technology**
 - SLC-NAND flash technology
- **Form-factor**
 - CFast™ Type I
- **Host interface**
 - 7 pins (data) + 17 pins (power)
 - CFast™ connector
- **Performance**
 - **Data transfer rate**
 - SATA 1.5Gb/s, 3.0Gb/s, 6.0Gb/s
 - **Sequential read**
 - 61.4 MB/sec (Max.)
 - **Sequential write**
 - 27.9 MB/sec (Max.)
- **Environmental**
 - **Operating temp.**
 - STD. 0°C~+70°C/IND. -40°C~+85°C
 - **Non-operating temp.**
 - STD. -20°C~+80°C/IND. -50°C~+95°C
 - **Humidity**
 - 10% ~ 95% non-condensing
 - **Vibration**
 - 70 Hz to 2K Hz, 20G, 3 axes
 - **Shock**
 - 0.5ms, 1500 G, 3 axes

- **Power consumption**
 - **Power requirement**
 - +3.3 V ± 5%
 - **Reading mode**
 - 240 mA (Max.)
 - **Writing mode**
 - 320 mA(Max.)
 - **Idle mode**
 - 110 mA (Max.)
- **Reliability**
 - **Wear-leveling**
 - Static wear-leveling algorithms
 - **TBW**
 - Up to 108 TBW at 2GB Capacity (Sequential Write)
 - **MTBF**
 - > 3,000,000 hours
 - **Erase counts**
 - Up to 60,000 times
 - **ECC**
 - 40 bits per 1024bytes block
- **Physical specification**
 - **Weight (Max.)**
 - Plastic frame : 10g
 - Rugged metal frame : 13g
 - **Dimension (WxLxH)**
 - 42.8 x 36.4 x 3.5 (mm)
- **Conformal coating**
 - Optional
- **Warranty**
 - **SLC STD. grade**
 - 3 years or within 60,000 erasing counts
 - **SLC IND. grade**
 - 5 years or within 60,000 erasing counts

❖ Part Number List

Standard plastic frame CFA			Optional rugged metal CFA		
Capacity	0°C~+70°C	-40°C~+85°C	Capacity	0°C~+70°C	-40°C~+85°C
1GB	SPCFA001G-JGCTC	WPCFA001G-JGITI	1GB	SRCFA001G-JGCTC	WRCFA001G-JGITI
2GB	SPCFA002G-JGCTC	WPCFA002G-JGITI	2GB	SRCFA002G-JGCTC	WRCFA002G-JGITI

❖ Part Number Decoder

X1	X2	X3	X4	X5	X6	X7	X8	X9	X10	X11	X12	X13	X14	X15	X16	X17	X18	X19	X20
----	----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Example

W	R	C	F	A	0	0	2	G	—	J	G	C	T	I	—	C			
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	--	--	--

X1 Grade

S : Standard grade operating temp. 0°C~+70°C
 W: Industrial grade operating temp. -40°C~+85°C

X2 The material of casing

P : Plastic frame
 R : Rugged metal frame

X3 **X4** **X5** Product category

CFA : CFast™ card

X6 **X7** **X8** **X9** Capacity

001G : 1GB
 002G : 2GB

X11 Controller

J : HERMES Series

X12 Controller version

A, B, C, D....G

X13 Controller grade

C : Commercial grade
 I : Industrial grade

X14 Flash IC brand

T : Toshiba SLC-NAND flash IC

X15 Flash IC grade

C : Commercial grade
 I : Industrial grade

X17 **X18** **X19** **X20** Reserved for specific requirements

C : Conformal coating (optional)

SLC
 aSLC
 MLC
 3D-NAND
 DRAM Module
 Adapter
 Card-drive